



**ADDENDUM NO. 2
INVITATION TO BID- 05ITB43665YC
FIRE APPARATUS TRACTOR DRAWN ARIAL (TDA)
FIRE APPARATUS PUMPER (SIDE MOUNT PUMP
PANEL)**

May 25, 2005

Dear Vendors:

This addendum is in reference to the INVITATION TO BID, Fire Apparatus. 05ITB438665YC.

**The following information is in response to a specific vendor question
regarding the subject BID; 05ITB438665YC**

Question:

Page 132 item 8.3 Telescoping Quartz Lighting. How many? text is confusing as it uses both singular and plural language.

Answer:

*****8.3 should read as follows:

8.3 Telescoping Quartz Lighting

Two lights shall be attached to the rear of the tractor cab, one on each side. Lights shall be side mounted, bottom raise telescoping, anodized aluminum pole. The telescoping pole shall have a four (4) foot extension with friction lock mechanism. The telescoping pole shall be pre-wired with heavy-duty retractile cord with pigtail extending out the bottom of the lower tube.

The telescoping light shall be Kwik Raze Magnafire 3000 model #KR-537-S or equal. The lights shall be mounted to allow personnel to raise the lights from the ground without having to climb on the apparatus.

Question:

Reference Page 100,

5.8, 5.9, 5.10, and 5.11 "Shelves, and trays.

Each paragraph refers to numbered compartments for amounts and locations.

Pages 106 and 107 describe compartments, however no reference to shelves or trays.

Bidders need information in order to bid the proper amount of shelves and trays.

Answer:

*****5.27 should read as follows:

5.27 Compartments

The Aerial body is design to provide the maximum amount of compartment space possible, yielding 27" deep lower compartments and 14" high air pack type compartments. This is a critical feature when trying to store PPV fans, saw boxes, etc in body compartments.

All compartments less than 45" in height shall have a minimum of two (2) adjustable shelves and one (1) 500 lbs. slide out tray. Compartments in excess of 46" shall have a minimum of three (3) adjustable shelves and one (1) 500 lbs. slide out tray. Transverse compartment will be laid out in the same manner with the exception of one (1) 1000 lbs. slide out tray in place of one (1) 500 lbs slide out tray. Exact lay out to be discussed at pre-build conference.

Question:

Items 3.36, 4.6.4, and 4.6.5. These all call for sirens. It is most unusual that a department would call for three (3) separate sirens on a single fire pumper. We will be pressed for space to mount all sirens and speakers on or recessed in the front bumper along with the air horns.

Item 5.16 text reads "ADD MONITOR HERE, INCLUDE ACCESSORIES" does this reference 9.2

"Appliances" item # 2? Are we to price in the space provided in 9.2 and just add the text to proposal? Or, do you intend bidders to include the price in the proposal and indicate "standard" in the space provided in 9.2?

Answer:

3.36 Should be omitted.

Item 5.16 should read as follows...

5.16 Three Inch Deck Gun Discharge

A deck gun discharge shall be provided in the hose pan area above the pump area. The deck gun will be operated by an Akron 9305 series valve controller and pressure/flow meter and Akron 8600 series valve. Manufacture shall supply one (1) Akron Apollo Hi-Riser Monitor Style 3433 complete. To include dual inlet ground base, liftoff, direct mount, Akromatic 5060 fog nozzle and set of 2499 stack tips

Question:

Item 3.40 Additional A/C. we cannot locate a unit that has a 57,000 btu rating. We suspect this may be an error. Coleman has a unit that is rated at 13,500 btu and it exceeds the specified 305 cfm (310). Can you supply a mfr. and model # so we know what to propose?

Answer:

Item 3.40 should read as follows...

3.40 Cab Additional A/C

In addition to factory air conditioning, one (1) roof mounted air conditioner/ heater unit, such as Coleman 13,500 BTU Mach III or equal, shall be installed. The unit shall operate at a maximum of 1800 watts, 120 volt single phase load. The air conditioner unit shall operate from both shore power and generator power. A variable speed fan shall supply a minimum of 305 CFM air flow capacity. Opening in roof shall be properly reinforced to support air conditioners and be supplied with a 1" rise to minimize moisture and condensation under the unit.

For additional information regarding this addendum contact Al Micah Phillips, Assistant Purchasing Agent at (404) 730-4214.

The undersigned proposer acknowledges receipt of this addendum by returning (1) copy with their bid. Failure to return a signed copy of this addendum with your bid could render your bid to be non-responsive.

Except as provided herein, all terms and conditions in the bid referenced above remain unchanged and in full force and effect.

Sincerely,



Al Micah Phillips
Assistant Purchasing Agent

ACKNOWLEDGEMENT OF ADDENDUM

COMPANY NAME: _____ Signature: _____
NAME: _____ TITLE: _____ DATE: _____